



Our product range includes baling wire, also called strapping wire. This wire is a soft-annealed iron wire that is oiled or not oiled according to customer requirements. It is mainly used by companies that have to compress material or store material in a space-saving way. The main users are the recycling, packaging, paper and printing industries. We offer various ring sizes with different dimensions\* to provide you with flexibility. We are able to ensure short delivery times because the baling wire is manufactured in our factory in Germany.

## DIMENSIONS

MM	M / KG
1.80	50.0
2.00	40.5
2.20	33.5
2.50	26.0
2.80	20.7
3.00	18.0

## SURFACES

MM	M / KG
3.10	16.9
3.20	15.8
3.40	14.0
3.60	12.5
3.80	11.2

Black annealed	Oiled	Not oiled
Galvanised	Oiled	Not oiled

## BALING WIRE UNIT QUANTITY

SPOOLED RINGS	OUTER Ø MM	INNER Ø MM	HEIGHT MM
20 kg	250	95	95
40 kg	336	206	152

RINGS / ROSETTES	OUTER Ø MM	INNER Ø MM	HEIGHT MM
100 kg	750	450	150
250 kg	750	450	300
500 kg	750	450	600
1000 kg	750	450	900

## LOOP WIRE UNIT QUANTITY

Length:	500 – 5,000 mm
Packaging:	In bundles of approx. 25 kg or large bundles of approx. 1,000 kg. Also available reeled and delivered on pallets.

## JAMLOCK BALE TIES

Length:	1,350 – 5,700 mm
Packaging:	In bundles of 50 pieces or bundled to large bundles. Also available reeled and delivered on pallets.

\* Other dimensions and unit quantities possible on request.