

FLAT STITCHING WIRE



Flat stitching wire is also called “iron wire” or “galvanised wire”. Flat stitching wire has many applications. The most well-known application is certainly the manufacture of office material that can be found in every office. It is available in bare, copper-coated or galvanised surfaces and with different dimensions. Different spool types and sizes are also available.*


DIMENSIONS

NO.	MM	M / KG
0 / 26	0.70 X 0.30	650
I / 25	0.75 X 0.35	540
II / 24	0.75 X 0.45	420
III / 23	0.75 X 0.55	345
IV / 22	0.80 X 0.65	295
V / 21	0.90 X 0.65	250
VI / 20	0.96 X 0.78	200
VII / 19	1.15 X 0.90	150
VIII / 18	1.25 X 1.05	115
IX / 17	1.50 X 1.16	90

SURFACES
bright
Copper-coated
Galvanised
reddish bright

QUALITIES
Standard
Steel


SPOOLS



Spool D 135	
Weight	2 kg
A	135 mm
B	55 mm
C	16 mm
D	49 mm



Spool D 140	
Weight	3 kg
A	140 mm
B	90 mm
C	16 mm
D	90 mm



Spool D 150	
Weight	3 kg
A	150 mm
B	55 mm
C	18 mm
D	49 mm



Spool BP 4	
Weight	4.5 kg
A	155 mm
B	65 mm
C	18 mm
D	63 mm



Spool D 150 D	
Weight	5 kg
A	150 mm
B	55 mm
C	18 mm
D	100 mm




Spool SD 200 K	
Weight	5 kg
A	200 mm
B	105 mm
C	50 mm
D	55 mm



Spool SD 300	
Weight	15 kg
A	300 mm
B	210 mm
C	52 mm
D	102 mm



Spool BB 20	
Weight	17 kg
A	200 mm
B	110 mm
C	32 mm
D	180 mm



* Other dimensions and unit quantities possible on request.